

MATERIAL SAFETY DATA SHEET – SURECOAT ANTI-GRAFFITI WATER REPELLENT

Effective Date: 05/01/2009

Emergency #: 877-823-7873

SECTION I. IDENTIFICATION

PRODUCT NAME: Graffiti Repellent

CHEMICAL NAME & SYNONYMS: Anti-Graffiti Water Repellent / Water-based Mixture of Modified Siloxanes/Silanes

PROCESSORS NAME: SureCoat Systems 2940-A E. La Jolla Street Anaheim, CA 92806 Phone: (877) 823-7873

CAS #: Not Issued

CHEMICAL FAMILY: Water Solution of Modified Siloxanes/Silanes and Paraffin Wax

CHEMICAL FORMULA: Proprietary Water-based Mixture of silanes, siloxanes and paraffin wax.

SECTION II. COMPONENTS

INGREDIENTS

- Siloxanes/Silanes
- Paraffin Wax
- Trace chemicals
- Water

CAS NUMBER

Mixture
64742-43-4

% BY WT

12%
15%
< 1.0%
Balance

* The concentrations shown in the substance list are maximum or ceiling levels (weight %) to be used for calculations for regulations.

SECTION III. HEALTH HAZARDS

NFPA 704 CODES: 0=Minimal, 1=Slight, 2=Moderate, 3=Serious and 4=Severe

HEALTH (BLUE)

NFPA: 1
HMIS:1

FLAMMABILITY (RED)

NFPA: 0
HMIS: 0

REACTIVITY (YELLOW)

NFPA: 0
HMIS: 0

CLOTHING

NFPA:
HMIS: PP = B

ACUTE EFFECTS OF OVEREXPOSURE:

- **EYE:** Mildly irritating to the eyes.
- **SKIN:** May cause slight skin irritation.
- **INHALATION:** Breathing mist may cause mild irritation to upper respiratory tract.
- **INGESTION:** None known. DO NOT TAKE INTERNALLY. Seek immediate medical attention.

CHRONIC EFFECTS OF OVEREXPOSURE: Repeated prolonged skin contact may produce irritation.

OTHER HEALTH EFFECTS (MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE): People with sensitive skin can experience aggravated skin irritation. No other known applicable information.

SECTION IV. FIRST AID MEASURES

EMERGENCY FIRST AID PROCEDURES:

- **EYE:** Immediately flush eyes with running water for at least 15 minutes. Seek immediate medical attention.
- **SKIN:** Minimal effects on contact. Wash skin with soap and water. If irritation occurs or continues, seek medical attention.
- **INHALATION:** Remove to fresh air. If breathing difficult, seek immediate medical attention.
- **INGESTION:** Do not take internally. Drink large quantities of milk or water. Do not induce vomiting. Seek immediate medical attention

SECTION V. FIRE AND EXPLOSION HAZARD DATA

Does not support combustion and is not considered a fire or explosive hazard. When involved in a fire, it may emit vapors containing the siloxane containing materials, carbon oxides and silicon dioxide. These materials should be considered irritants. In addition, the silicon dioxide dust has a PEL of 6 mg/m³ and an ACGIH Total Dust of 10 mg/m³. It is possible for product to create SiO₂ dust levels greater than these PEL and AVGIH limits when decomposed in a fire or explosion. For these reasons, fire fighters should wear self-contained breathing apparatus and full protective clothing. Heated closed containers may burst due to steam pressure. Cool containers with water.

SECTION VI. SPILL, LEAK & DISPOSAL PROCEDURES

Floors may be slippery; use care to avoid falling. Contain spills immediately with inert material to prevent waterway entry. Transfer liquids and solid diking materials to suitable containers for recovery or appropriate disposal.

SECTION VII. HANDLING AND STORAGE

Handle in a well ventilated area. Maintain positive pressure in interior of occupied buildings during exterior application and close fresh air intakes in area of application. Avoid inhaling vapors and mists, and getting in eyes, on skin or on clothing. Appropriate protective clothing necessary to prevent repeated or prolonged skin contact should be worn. Skin contact should be minimized by wearing impermeable gloves. Resistant boots should be worn where spills or splashing can occur. Wash hands and other contaminated areas thoroughly with soap and water after handling this product and before eating or smoking. Wash contaminated clothing and equipment thoroughly before reuse. Safety showers and eye stations should be available to employees.

Normal warehouse storage in a closed container is adequate. Storage temperature should be above freezing and below 120°F. Drain equipment and flush with water to clean.

MSDS GRAFFITI & WATER REPELLENT

SECTION VIII. PERSONAL PROTECTION

Appropriate personal protective equipment necessary to prevent repeated or prolonged contact should be worn. Mechanical ventilation is recommended. Avoid breathing mist or vapors. Where high concentrations of mist occur, a respirator with appropriate dust and mist removal capabilities is recommended. Eye protection, resistant clothing and resistant boots should be worn where spills or splashing can occur. This may include goggles, face shield, water resistant clothing and rubber boots. A single prolonged skin exposure is not likely to result in skin irritation or absorption through the skin in harmful amounts. Wash contaminated clothing before reuse. Do not take internally. An eye wash station should be available.

SECTION IX. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Cream

pH: (Typical) 6

VAPOR PRESSURE, at 20 deg. C: 17.5 mm Hg

SOLUBILITY IN WATER, by wt.: 100%

PHYSICAL STATE: Liquid

ODOR: None or low

BOILING POINT, 760 mm Hg: 212 F, 100 C

LIQUID DENSITY: Approx. 1 g/cm³ at 25C

SPECIFIC GRAVITY (H₂O = 1): 1

VICOSITY: Approx. 100 mPa*s

SECTION X. STABILITY AND REACTIVITY

Reacts with silicate in concrete and masonry in the presences of ultraviolet light and moisture forming bonds with the substrate in normal use. The organic content of the aqueous mixture will react with bases, acids and oxidizers producing heat, polymers and oxidation by-products. Atomization, vaporization or combustion forms aerosols which can carry siloxane containing materials carbon oxides and silicon dioxide into the atmosphere. Hazardous polymerization will not occur.

SECTION XI. TOXICOLOGICAL INFORMATION

This product is known to be a mild eye and upper respiratory irritant. OSHA PEL and ACGIH TLV have not been established; however, the low vapor pressure of the siloxane containing materials in the product should produce air concentrations below expected exposure limits. The LD50 has not been determined but should be relatively high based upon typical silicone toxicity. Do not take internally, avoid breathing mist and minimize eye and skin contact. **HEALTH HAZARD CATEGORIES:** None of the product's ingredients are found on any lists of hazardous, carcinogenic or banned chemical agents or materials generated by them.

SECTION XII. ECOLOGICAL INFORMATION

There is little or no risk to surrounding vegetation during application and overspray on non-targeted areas can be easily removed with soap and water.

SECTION XIII. DISPOSAL CONSIDERATIONS

The material is non-hazardous. Small quantities may be cleaned with soap and water and then flushed to a sanitary or industrial sewer. Absorbent material containing small amounts of the material may be disposed in appropriate land fills. Disposal of large quantities should comply with applicable disposal permits. Do not introduce large amounts into purification plants..

SECTION XIV. TRANSPORT INFORMATION

DOT SHIPPING NAME (49CFR 172.101): Non Flammable Liquid, NOS, Water Based Mixture of Siloxanes
(Organic silicon/oxygen compounds)

- **DOT ID# (49CFR 172.101):** Non-Regulated

- **MARKING:** None Required

- **PLACARD:** None Required

-**International Harmonic System Code:** 3910.00.00.00

- **DOT HAZARD CLASS:** Non Flammable Liquid, NOS

- **LABEL:** None Required

- **HAZARD (29 CFR 1910.1200):** Non-Flammable

SECTION XV. REGULATORY INFORMATION

FEDERAL This product is non-hazardous under the OSHA Hazard Communication Standard (29 CFR 1910-1200). All components are on the Confidential or Non-Confidential TSCA Inventory List. The ingredients of this product are listed on the Toxic Substances Control Act (TSCA) inventory and do not have special toxic substances warning requirements.

None of the components in this product require notification of the National Response Center under the Comprehensive Environmental Response Compensation, and Liability Act of 1980 (CERCLA) per 40 CFR 302.4.

None of the components in this product require reporting under Superfund Amendment and Reauthorization Act of 1986 (SARA) Title III as emergency planning or release reporting per 40 CFR 355 (used for SARA 302, 304, 311 and 312). The components also do not require annual reporting as a toxic chemical under SARA Title III per 40 CFR 372 (for SARA 313). This product contains no chemicals subject to SARA Title III, Section -13, Part 372 reporting requirements.

STATE RIGHT-TO-KNOW: Under **California Proposition 65**, this product contains no listed substances at levels which would require a warning as a product known to cause cancer, birth defects or other reproductive harm. Under the Massachusetts Right-To-Know Law, this

product contains no listed substances at levels that require reporting per the Substance List. __Under the **Pennsylvania Right-To-Know Law**, this product contains no listed substances at levels that require reporting per the Hazardous Substance List.

SECTION XVI. OTHER INFORMATION

All terms and abbreviations have been defined in various government publications, or are standard chemical terms used by IUPAC.

The data and recommendations herein are based upon our research and the research of others, and are believed to be accurate. However, no warranty or guarantee of their accuracy is made; and the products are distributed without warranty, expressed or implied, included the limited warranties of merchantability of fitness for particular purpose.

Neither this data sheet nor any statement contained herein grants or extends any license, express or implied, in connection with patents issued or pending which may be the property of the manufacturer or others. The manufacturer makes no warranties, express or implied, as to the accuracy or adequacy of the information contained herein. The manufacturer shall not be liable to the vendee, the vendee's employees or anyone for any direct, special or consequential damages arising out of or in connection with this accuracy, adequacy or furnishing of such information.