



Graffiti Stripper

Water-Based Multi-Surface Remover

BENEFITS

- **Effective on many materials**
- **Gel consistency reduces spills and waste**
- **Softens coatings**
- **No-fumes or caustics**
- **Water-soluble**
- **Biodegradable. VOC less than 400 g/L**

DESCRIPTION

SureCoat Graffiti Stripper is a non-flammable, non-toxic, easy to use water-based graffiti remover.

CHARACTERISTICS

Clear thixotropic gel with a mildly sweet odor.

USAGE:

Safe to use on glass, masonry, metal, plaster, fiberglass, and wood. Test application should be applied to determine suitability.

The low-volatility nature of SureCoat Graffiti Stripper maintains a very slow evaporation rate, allowing it to remain on the surface to work and soften coatings. Depending on the nature of the coating to be removed, product will soften or wrinkle coatings, usually within 20-30 minutes.

NOTE: Not all coatings, such as cross-linked epoxies and urethanes can be removed with this product. Perform test application.

PRECAUTIONS:

Applicators should wear eye protection and appropriate clothing and gloves. Consult MSDS sheet. Protect all non-targeted adjacent surfaces, window glass, vehicles, aluminum, paint films and plant life.

APPLICATION:

Shake well before using. Do not dilute or alter. Protect from freezing. Always test each type of surface, paint coating and graffiti stain for suitability and results before the overall application. Let tests dry thoroughly before inspection.

Best results are obtained when applied at surface temperature between 80° and 100° F. The colder the conditions, the slower SureCoat Graffiti Stripper works.

Apply liberally to the graffiti using a brush or airless spray equipment. Apply a uniform coat. Let stripper dwell on the surface for 10-20 minutes depending on the type and severity of the graffiti tag and type of surface.

Periodic agitation with a stiff bristle brush improves product penetration through the graffiti residue as possible from the surface. Re-application and cycle cleaning may be necessary.

Thoroughly pressure-wash the surface with water (approximately 400-600 psi, depending upon surface). For best removal results, use of hot water is recommended.

Let the surface dry completely. Before applying any new anti-graffiti coating, ensure that all graffiti stripper has been rinsed away.

COVERAGE: 50-100 sq. ft. per gallon estimated coverage rates depend on surface texture and porosity.

COMPLIANCE: V.O.C. Less than 400g/L

For technical assistance call a SureCoat Systems' Product Specialist at 877-823-7873.

Disclaimer/Warranties: Neither manufacturer nor seller have any knowledge or control concerning the purchaser's use of the product. No expressed warranty is made by manufacturer or seller with respect to any use of the product or container that the product comes in. No implied warranties including, but not limited to, an implied warranty of merchantability or an implied warranty of fitness for a particular purpose are made with respect to the product. User shall rely on his own information and tests to determine sustainability of the product for the intended use and user assumes all risk and liability resulting from use of this product. Neither manufacturer nor seller assume any liability for personal injury, loss or damage resulting from the use of the product. We do not suggest or guarantee that any hazards listed herein are the only ones which may exist. In the event that the product shall prove defective, buyer's exclusive remedy shall be that the seller or manufacturer shall, upon written request of buyer, replace any quantity of the product which is proven to be defective or shall, at its option, refund the purchase price of the product upon return of the product. Manufacturer shall not be responsible for use of this product in a manner to infringe on any patent held by others. (Revised 04-2016)

www.surecoatsystems.com

Phone: (714) 633-5706 • Toll Free: (877) 823-7873 • Fax: (714) 683-0748