



# Stain Repellent

High Performance – Chemical Resistant

## BENEFITS

- Repels stains, oil, food products, and graffiti. Surface will continue to breathe.
- No change in surface appearance. Deep penetration into the substrate.
- Excellent resistance to water intrusion. Exhibits good beading effects.
- High resistance to alkali attack. High resistance to wind-driven rain.

## DESCRIPTION:

SureCoat Systems Stain Repellent (SR) is clear, penetrating, breathable and VOC compliant. SR is a chemical resistant, water, oil and graffiti protection treatment for concrete, porous tile, paving, grout, some natural stone and other building materials. SR penetrates the surface and bonds chemically into the substrate, resulting in long term protection by reducing the ingress of water-borne and oil-based contaminants into the surface. SR is an excellent treatment around areas where food products such as mustard, ketchup, grease, milk, wine, beer and soft drinks are present. It is also suitable for use as an anti-graffiti treatment. SR keeps treated indoor and outdoor surfaces clean and easier to maintain.

## APPLICATIONS:

SR is a chemical resistant, water, oil and graffiti protection treatment for concrete, porous tile, paving, grout, some natural stone and other building materials. SR is suitable for a wide variety of applications, including building facades, floors, walls, swimming pool surrounds, patios, garages, kitchens and entertaining areas.

## ADVANTAGES:

SR is designed to work without changing the natural appearance of the surface and is able to repel stains, oil and food products as well as graffiti. It is suitable for indoor and outdoor use and is able to seal hairline cracks up to 0.3 mm. SR does not flake or peel.

## LIMITATIONS:

Not intended for below-grade waterproofing. Product should not be applied if the surface temperature is below 40° F or above 100° F, if rain is expected within six hours following application, or if high winds or other conditions prevent proper application. If rain has preceded the application, the surface should be allowed to dry at least 24 hours. Caution should be taken with windows, motor vehicles, vegetation and adjacent surfaces. Check compatibility before application

## PRECAUTIONS:

SR should be kept closed when not in use and should be stored at temperatures between 35° F and 120° F. Care should be taken to prevent moisture condensation in the container. Please refer to the Material Safety Data Sheet for more detailed information. During application, precautions should

be taken to protect the surrounding area from overspray and run off. Product will not etch glass but will leave a residue on non-porous surfaces.

**COVERAGE:** Approx. 80-300 square feet per gallon.

## APPLICATION METHOD:

All surfaces must be cleaned to remove all traces of dirt, dust, efflorescence, mold, salt, grease, oil, asphalt, laitance, curing compounds, paint, coatings and other contaminants. Acceptable surface cleaning methods include shot-blasting, sandblasting, water-blasting and chemical cleaners.

Before applying, it is recommended that preliminary tests be carried out to determine usage and to test the effectiveness of the treatment. Depending on the porosity of each designated surface, coverage rates can vary.

SR should be applied by low-pressure (15 to 25 psi) pumping equipment with a wet fan type spray nozzle. Alternate methods include nap roller (1”) or by brush.

Horizontal surfaces should be treated until material puddles or stands on the surface. After ten minutes sweep, squeegee, or mop any remaining material to dry areas.

Vertical surfaces should be treated from top down using a low-pressure sprayer with a fan-type nozzle or with a roller with a minimum 1/2” nap. Flood surface until excess product runs down 6-8 inches below spray or roller pattern. A wet-on-wet re-application within 2-3 minutes is recommended for maximum coverage.

**For technical assistance call a SureCoat Systems’ Product Specialist at 877-823-7873.**

Disclaimer/Warranties: Neither manufacturer nor seller have any knowledge or control concerning the purchaser’s use of the product. No expressed warranty is made by manufacturer or seller with respect to any use of the product or container that the product comes in. No implied warranties including, but not limited to, an implied warranty of merchantability or an implied warranty of fitness for a particular purpose are made with respect to the product. User shall rely on his own information and tests to determine sustainability of the product for the intended use and user assumes all risk and liability resulting from use of this product. Neither manufacturer nor seller assume any liability for personal injury, loss or damage resulting from the use of the product. We do not suggest or guarantee that any hazards listed herein are the only ones which may exist. In the event that the product shall prove defective, buyer’s exclusive remedy shall be that the seller or manufacturer shall, upon written request of buyer, replace any quantity of the product which is proven to be defective or shall, at its option, refund the purchase price of the product upon return of the product. Manufacturer shall not be responsible for use of this product in a manner to infringe on any patent held by others. (Revised 04-2016)

[www.surecoatssystem.com](http://www.surecoatssystem.com)

Phone: (714) 633-5706 • Toll Free: (877) 823-7873 • Fax: (714) 683-0748