

SureSkrub-Multi-Purpose Cleaner Degreaser

Description

SureSkrub is a concentrated cleaner degreaser which is extremely effective cleaning a wide variety of surfaces. From vinyl and leather to automobile motors and chassis, its powerful formula easily cuts through the toughest grease, oil and built up grime, leaving surfaces clean and beautiful looking. The more difficult the cleaning situation, the better SureSkrub is to use.

Easy to Use

All you do is dilute it and apply. SureSkrub does the job cleaning and after being given enough time to work, it is rinsed off with water. See more information below.

Cost Effective

Because it is highly concentrated, a little SureSkrub goes a long way. On virtually any cleaning job, it is easy and economical to use.

Biodegradable

In spite of its incredible strength, SureSkrub is designed to be environmentally friendly. Its biodegradable formulation readily breaks down; and it does not cause smog, acid rain nor is harmful to the ozone layer.

For Roofing

SureSkrub can be used full strength or diluted on all types of roof materials including BUR, Mod/Bit, EPDM, metal, tar, TPO, PVC and other Single Ply. Dilution ratio depends on the condition of the roof.

Technical Data

- Appearance/Order: Medium red-pink colored liquid with mild fragrant aroma.
- Coverage: Varies widely depending on what is being cleaned and the type of surface it is being used on. Typically Roof Systems will require 1 gallon per 500-1,000 square feet.
- Packaging: SureSkrub is available in 1 gallon jugs and 5 gallon pails.
- Storage/Shelf Life: Keep containers sealed when not in use and store in a cool, dry place. If not permitted to evaporate, shelf life is indefinite.

Application

1. **Mix SureSkrub using one of the following dilution ratios:**
 - **Light Commercial / Retail** (little to no stain) 25% SureSkrub and 75% water
 - **Commercial / Light Industrial** (some stain to moderate condition) 50% SureSkrub and 50% water
 - **Food Processing / Restaurant** (heavy saturation, i.e. oil, fats, chemicals) Full StrengthThis can be done separately in a bucket and using a sponge mop or sprayer to apply it. SureKlean can be applied through the downstream injector system of a pressure washer.
2. **Agitate built up grime with a stiff bristled brush.** Single ply roof materials should be agitated with a stiff bristled brush or scotch-brite pad. A floor scrubber with a scotch-brite pad is great for cleaning single ply systems; this helps to disperse the chemical, allowing it to work its way down into the surface for a deep clean. **Do not use steel wool** when cleaning roofs.
3. **Give SureSkrub time to work.** On light dirt like the kind found on vinyl, leather and most painted surfaces this probably takes no more than a few seconds. Difficult cleaning situations like roof surfaces with organic matter or degraded glaze on single ply roof materials, grimy car motors, heavy machinery or oil saturated concrete may need 30 minutes or longer to best results. Roof surfaces should be agitated a second time.
4. **Rinse the surface with water.** A pressure washer is recommended and usually works best for this procedure. When using on existing roof materials that are going to be completely reconditioned with a SureCoat Roof System, rinsing with a pressure washer is required.

Safety

Wear rubber gloves and safety goggles when handling SureSkrub. If it gets on skin or into eyes, rinse thoroughly with water. See Material Safety Data Sheet for more detailed hazard evaluation and safety information.

Notice

The information contained herein is based on our own research and the research of others, and it is provided solely as a service to users. It is believed to be accurate and the best of our knowledge. However, no guarantee of its accuracy is made, and it is not intended to serve as the basis for determining this product suitability in any particular situation. For this reason purchasers are responsible to make their own tests and assume all risks associated with using this product.